


OXYGEN METER

Model : DO-5510HA

ISO-9001, CE, IEC1010

FEATURES

- * The polarographic type oxygen probe with an incorporated Temp. sensor, high precision measurement for Dissolved Oxygen(DO), Oxygen in air(O₂) & Temp. measurement.
- * Heavy duty dissolved oxygen probe, probe head can connect with BOD bottle.
- * Automatic Temp. compensation from 0 to 50 °C for sensor probe.
- * Build in " % SALT " & " Mountain Height " compensation adjustment button.
- * Microprocessor circuit.
- * Records Maximum, Minimum value.



Lutron

LUTRON ELECTRONIC

Supplied in Australia by Instrument Choice
Call our scientists on 1300 737 871
www.instrumentchoice.com.au

The Art of Measurement

OXYGEN METER

Model : DO-5510HA

GENERAL DESCRIPTIONS

This Digital Oxygen Meter is supplied with a polarographic type probe with an incorporated Temp. sensor which serves for precise Dissolved Oxygen(DO), Oxygen in air(O₂), Temp. measurement. Applications for Aquarium, Medical research, Agriculture, Fish hatcheries, Laboratory, Water conditioning, Mining industry, Schools & Colleges, Quality control...

FEATURES

* The polarographic type oxygen probe with an incorporated Temp. sensor, high precision measurement for Dissolved	* Microprocessor circuit assures high accuracy and provides special functions and features.
* Oxygen(DO), Oxygen in air(O ₂) & Temperature measurement.	* Multi-display, show oxygen & Temp. at the same time.
* Heavy duty dissolved oxygen probe, probe head can connect with BOD bottle.	* Records Maximum, Minimum and Average readings with RECALL, data hold.
* Automatic Temp. compensation from 0 to 50 °C for sensor probe.	* Auto power off saves battery life. Powered by 006P DC 9V battery.
* Build in " % SALT " & " Mountain Height " compensation , adjust the factor by push the button on the front panel.	* Build in temperature , °F measurement. * Use the durable, long-lasting components, including a heavy duty & compact ABS-plastic housing case.

SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.	Over input indication	Indication of "- - - -".	
Display	Dual function meter's display, 13 mm(0.5"). Super large LCD display with contrast adjustment for best viewing angle.	Operating Temperature	0 to 50 °C (32 to 122 °F).	
Measurement & Range	Dissolved Oxygen	0 to 20.0 mg/L(liter).	Operating Humidity	Max. 80% RH.
	Oxygen in Air	0 to 100.0 %.	Sample Time	Approx. 0.4 sec.
	Temperature	0 to 50 °C.	Power Supply	006P DC 9V battery(Heavy duty type).
Resolution	Dissolved Oxygen	0.1 mg/L.	Power Current	Approx. DC 6.6 mA.
	Oxygen in Air	0.1 % O ₂ .	Weight	335 g/0.74 LB (batteries & probe included)
	Temperature	0.1 .	Size	Main instrument: 185 x 78 x 38 mm (7.3 x 3.0 x 1.5 inch). Oxygen probe : 190 mm x 28 mm Dia. (7.5" x 1.1" Dia.)
Accuracy (23 5)	Dissolved Oxygen	0.4 mg/L.	Accessories included	Oxygen probe(OXPB-11)..... 1 PC.
	Oxygen in Air	0.7% O ₂ .		Carrying case..... 1 PC.
	Temperature	0.8 °C /1.5 °F.		Operation manual..... 1 PC.
Sensor Structure	The polarographic type oxygen probe with an incorporated temperature sensor.		Optional Accessories	Spare Probe head with Diaphragm OXHD-04..... 2 set
Probe Compensation & Adj.	Temperature	0 to 50 °C, Automatic		Probe-filling Electrolyte OXEL-03..... 1 set
	Salt	0 to 39 % Salt		
Memory Recall	Height(M. T.)	0 to 3900 meter		
Power off	Records Maximum, Minimum and Average readings with RECALL.			* Oxygen probe..... OXPB-11
	Auto power off saves battery life, or manual off by push button.			* Spare Probe head with Diaphragm setOXHD-04
				* Probe-filling Electrolyte..... OXEL-03

* Appearance and specifications listed in this brochure are subject to change without notice.

0610-DO5510HA