



5 mm		8 mm	
embeddable		non embeddable	
9954-2200	9954-1900		
9954-2600	9954-2500		
90 V ... 250 V AC			
50/60 Hz			
5 mA			
180 mA			
≤ 8 V			
≤ 3 mA / 230 V		≤ 1,5 mA / 110 V	
1 A			
15 Hz / (ohmic load 150 mA)			
≤ 15 %			
≤ 10 %			
≤ 10 %			
Nickel-plated brass			
PBTP			
Cable 3 x 0,5 mm²			
XXXX-xx00 / XXXX-xx02			
IP 67			
-25 °C ... +70 °C			
●			

5 mm		8 mm	
embeddable		non embeddable	
9954-2268	9954-1968		
9954-2668	9954-2568		
90 V ... 250 V AC			
50/60 Hz			
5 mA			
180 mA			
≤ 8 V			
≤ 3 mA / 230 V		≤ 1,5 mA / 110 V	
1 A			
15 Hz / (ohmic load 150 mA)			
≤ 15 %			
≤ 10 %			
≤ 10 %			
Nickel-plated brass			
PBTP			
Plug connection			
-			
IP 67			
-25 °C ... +70 °C			
●			

10 mm		15 mm	
embeddable		non embeddable	
9956-1500	9956-1400		
Plug connection			
9956-1568	9956-1468		
9956-1900	9956-1800		
Plug connection			
9956-1968	9956-1868		
90 V ... 250 V AC			
50/60 Hz			
5 mA			
180 mA			
≤ 8 V			
≤ 3 mA / 230 V		≤ 1,5 mA / 110 V	
1 A			
15 Hz / (ohmic load 150 mA)			
≤ 15 %			
≤ 10 %			
≤ 10 %			
Nickel-plated brass			
PBTP			
Cable 3 x 0,5 mm²			
or plug connection			
XXXX-xx00 / XXXX-xx02			
IP 67			
-25 °C ... +70 °C			
●			