

# ODV-3-340180-3F1A-MN

## Optidrive Eco VFD Datasheet

### 7.5 kW (10 HP), 18 A, 380-480 V, 3PH

IP66 Non Switched Outdoor Variable Frequency Drive with EMC Filter and TFT Display



#### Input Ratings

|                             |           |
|-----------------------------|-----------|
| Supply Voltage              | 380-480 V |
| Input Phases                | 3         |
| Supply Current Continuous   | 14 A      |
| Supply Fuse or MCB (Type B) | 16 A      |

#### Output Ratings

|                     |                    |
|---------------------|--------------------|
| Motor Output Rating | 7.5 kW (10 HP)     |
| Output Voltage      | 0 – Supply Voltage |
| Output Current      | 18 A               |

#### Cable Information

|                        |                                |
|------------------------|--------------------------------|
| Max Supply Cable Size  | 8 mm <sup>2</sup> (0.01 sq in) |
| Max Motor Cable Size   | 8 mm <sup>2</sup> (0.01 sq in) |
| Max Motor Cable Length | 100 m (328 ft)                 |

#### Factory Build Options

|                  |                           |
|------------------|---------------------------|
| EMC Filter       | Internal EMC              |
| Brake Transistor | No Brake Transistor       |
| Enclosure        | IP66 Non Switched Outdoor |
| Display          | TFT Display               |
| PCB Coating      | Standard                  |

#### Dimensions

|         |                    |
|---------|--------------------|
| Size    | 3                  |
| Height  | 310 mm (12.2 in)   |
| Width   | 211 mm (8.31 in)   |
| Depth   | 225 mm (8.86 in)   |
| Weight  | 6.6 kg (14.55 lbs) |
| Fixings | 4 x M4             |

#### Packaged Dimensions

|        |                    |
|--------|--------------------|
| Height | 305 mm (12.01 in)  |
| Width  | 270 mm (10.63 in)  |
| Depth  | 440 mm (17.32 in)  |
| Weight | 7.6 kg (16.76 lbs) |



**Buy this drive or get more information**

Find your local sales partner on  
[invertekdrives.com](http://invertekdrives.com)





**eco**  
**OPTIDRIVE™**

AC Variable Speed Drive

## PUMP CONTROL


Energy efficient pumping with **OPTIFLOW™**

 **BACnet™**  
MS/TP  
built-in as standard

**Low Harmonic  
Design**  
EN 61000-3-12  
Compliant

0.75kW – 250kW / 1HP – 400HP  
**200–600V** Single & 3 Phase Input






## Energy Efficient Pumping

When a pump or pump set is selected, it must be suitable for operation during periods of maximum flow demand. In many applications, this maximum flow level may be rarely required, and as such the pump may operate for long periods at less than maximum flow capacity. By varying the speed of the pump to match the actual flow demand, significant energy savings are possible.

Optidrive Eco Pump has been designed to maximise the energy savings potential in pumping applications, whilst also providing significant additional benefits

in reduced installation costs, maintenance costs and downtime. Throughout all this, Invertek's "Ease of Use" philosophy ensures that advanced features are simple to commission, without requiring extensive, in depth knowledge of a huge number of parameters. Optidrive Eco Pump has a simple menu structure, and provides just the right amount of parameters to allow flexibility without over complication.

Overall, this provides the perfect balance of Easy to Install, Easy to operate, Advanced Pump Control.



### Energy Savings Calculator

Estimate your potential energy savings, CO<sub>2</sub> emissions and financial savings

[www.invertekdrives.com/calculator](http://www.invertekdrives.com/calculator)





Save Energy, Cut CO<sub>2</sub>



## Save Energy

**Eco vector operation**, based on Invertek's advanced motor control provides the most energy efficient operation of the pump, continually optimising the output to match the required flow with minimum energy consumption.

**Advanced sleep & wake functions** provide maximum energy savings by switching off the pump when not required

## Save Money

**OPTIFLOW™ technology** allows simple operation of multiple pump sets without the need for a PLC

**Pump blockage detection and cleaning** dramatically reduces pump maintenance requirements

**Built in PLC function** allows bespoke customised applications to be programmed directly in the drive

## Save Time

**Simple parameter set** allows fast commissioning of pump control systems

**Pump operating curve detection** automatically detects and monitors normal pump behaviour and is able to react when pumping conditions change

**Customisable OLED display** provides excellent visibility of drive status and operation in all conditions

### Key Features



#### ECO Vector Motor Control



#### Standard Induction Motors



Permanent Magnet AC Motors

Brushless DC Motors

Synchronous Reluctance Motors

#### Energy Optimised Design



#### Internal EMC Filter



#### Low Noise Operation



### Maximum Pumping Efficiency

#### Unique Eco Vector Sensorless Control


Optidrive Eco Pump uses advanced motor control technology, designed to provide the most energy efficient motor control possible. Operation with standard IM Motors, Permanent Magnet or Synchronous Reluctance motors is possible, all without requiring any feedback device or optional modules – simply change parameters to suit the connected motor, autotune and operate!

Eco Vector continuously adjusts in real time to provide the most efficient operating conditions for the load, typically reducing energy consumption by 2 – 3% compared to standard AC drives – providing similar long term costs savings to selecting a higher efficiency motor.

#### Energy Optimised Design

Optidrive Eco Pump up to frame size 5 are designed with film capacitors, replacing the traditional electrolytic capacitors used in the DC link. Film capacitors have lower losses, and also remove the need for AC, DC or swinging chokes, improving overall drive efficiency. Efficiency is improved by up to 4% compared to standard AC drives, whilst also reducing supply current total harmonic distortion (iTHD), improving the Real Power Factor and reducing total input current, leading to cost savings on installation through reduced cable and fuse ratings and smaller supply transformer rating.

Improved Efficiency, Reduced Lifetime Costs: e.g. for a 37kW load, operating 10 hours per day, 5 days per week, 50 weeks per year, improving the efficiency by just 1% will provide an energy saving > 900kWh per year.



# OPTIFLOW™ Multi-pump Control

Embedded control technology for multi-pump systems

## Flexible pump station control with no PLCs or pump control units

Setpoint Control

A standard  
feature on  
all drives

Independent pump  
control system

Optiflow  
Communications

← Feedback  
signal

### Pump Prime Mode



#### Pump Prime with Burst Pipe Detection

Pump prime mode allows starting of the pump in a safely controlled manner, to ensure consistent filling and pressurisation of pipe work and systems. Low pressure warnings are ignored during priming to allow the system to prime correctly, whilst a failsafe timeout prevents the pump from continuing to run in the event of a failure to prime. This helps to prevent the effects of water hammering (such as bursting water pipes) or damage to fountain / sprinkler heads.

The time limit, set for pump prime mode to complete, means that the pressure in the system must reach the minimum level within the set time. Failure of the system to pressurise would indicate a leak or burst pipe within the pump system and result in the Optidrive Eco Pump shutting down the pump. During normal operation the system pressure is still continuously monitored against the minimum level so that a burst pipe during normal operation will likewise result in the drive tripping 'low pressure' and shutting the pump down.

### Total Control

A single 'Master' drive acts to control and monitor system operation. Control connections are made to this drive only, saving installation time and reducing costs.

### Simple Connection

Additional drives connected on the system require a single RJ45 connection and basic commissioning, leading to time savings and simplified installation.

### Flexible Solution

The system can operate with up to five pumps in any configuration, e.g. Jockey Pump / Duty / Assist / Standby. Duty pumps are automatically rotated, ensuring maximum service life and system efficiency.



## Energy efficient pumping with **OPTIFLOW™**




### See **OPTIFLOW™** in action

Scan to watch the video or visit  
<http://youtu.be/9QQ89bQYdfs>

## Avoid Pump Downtime

### Blockage Detect/Clear

Optidrive Eco Pump can detect pump blockages and trigger a programmed cleaning cycle to automatically clear them, preventing downtime.



### Dry Run Protection

Optidrive Eco Pump can evaluate a pump's speed/power and shut it off or warn when the pump starts to run dry, protecting it from heat/friction damage.

### Motor Preheat Function

Optidrive Eco Pump features a motor preheat function to help ensure moisture is not permitted to collect on the motor in periods of inactivity and prior to motor start up. In addition, the motor preheat function can be used to keep condensation from developing on the motor as the motor cools down immediately following a stop. The feature is fully configurable, meaning the pump can be always available the instant it is required.

### Pump Stir Cycle

Triggered by a settable period of inactivity, a configurable cleaning cycle can be run to clear sediment, ensuring the pump is ready to run when needed.

## Summary

- All drives operate at variable speed for maximum energy efficiency.
- Operating time (Hours Run) is automatically balanced and duty pumps rotated
- Automatic system reconfiguration in the event of a pump fault (including the master pump).
- Continued system operation when drives are individually powered off (including the master drive).
- Communication and +24V control voltage shared between drives via a standard RJ45 patch lead.
- Independent maintenance indicators for each pump.
- Any pump can be switched to Hand operation at the touch of a button, and will automatically rejoin the network when switched back to Auto.
- For waste water applications each pump can be set for blockage/ragging detection and activate an automatic de-ragging/pump cleaning cycle.
- Optional mains isolator with lock-off for safe pump maintenance.
- Optiflow function configured through simple parameter set-up and intelligent drive self configuration.

## Consistent Flow

The required pressure and flow levels are maintained regardless of how many pumps are required. When demand increases, additional pumps are automatically brought on stream to assist and are switched off again when not required.

## Reduced Downtime

In the event of a fault, or if a pump needs to be isolated for maintenance, the system will automatically continue to operate with the remaining available pumps. The mains power can even be completely isolated from the Master drive without affecting operation of the Slave drives.

# Drive Features

A compact and robust range of drives dedicated to pump control



## Enclosure Options



## Multi Language Text Display

Installed as standard on all IP55 & IP66 models

- Clear multi-line text display
- Operates -10 to 50°C
- Wide viewing angle, effective in dark and light conditions
- Customisable display
- Multi-language selection






## Energy efficient pumping with **OPTIFLOW™**



### Noise Reduction



#### Quiet Motor Operation

High switching frequency selection (up to 32kHz) ensures motor noise is minimised.

#### Quiet System Mechanics

Simple skip frequency selection avoids stresses and noise caused by mechanical resonance in pipework.

#### Quiet Drive Operation

Long Life Dual Ball Bearing Fans provide quiet operation in addition to extended fan life.

### Noise Reduction through Speed Control


Optimising motor speed gives significant energy savings and reduces motor noise.

### Reduced Harmonic Current Distortion

Optidrive Eco Pump uses innovative design to improve overall efficiency whilst minimising the harmonic distortion levels. All drives designed for 3 phase power supply operation<sup>1</sup> up to frame size 5 utilise film capacitor in the DC link, providing exceptionally low harmonic current distortion without compromising efficiency. Frame size 6 and above include DC chokes and traditional electrolytic capacitors.

Optidrive Eco Pump product range complies with the requirements of EN61000-3-12.

#### Typical iTHD values at full and part load




It can be clearly seen that the reduced DC link capacitance significantly reduces the total harmonic distortion at full load, and has a much greater benefit at part load compared to a conventional DC choke or swinging choke. This results in reduced overall input current and reduced transformer heating effect.

#### Optidrive Eco Pump delivers

- Improved Efficiency, Reduced Lifetime Costs: e.g. for a 37kW load, operating 10 hours per day, 5 days per week, 50 weeks per year, improving the efficiency by just 1% will provide an energy saving > 900kWh per year
- Improved True Power Factor – No additional charges etc.
- Lower Mains Supply Current

#### Power factor comparison



Optidrive Eco offers improved power factor over conventional VFDs under all loads.

<sup>1</sup> 200V and 400V

# Options & Accessories

Peripherals to help integrate Optidrive Eco Pump with your pumping systems



## Optistick Smart



### Rapid Commissioning Tool

- Allows copying, backup and restore of drive parameters
- Provides Bluetooth interface to a PC running OptiTools Studio or the OptiTools Mobile app on a smartphone
- Onboard NFC (Near Field Communication) for rapid data transfer

**OPT-3-STICK-IN**

## Optipad



### Remote Keypad & TFT Display

IP55 panel mount operator interface.

- Clear multi-line text display
- Multiple language select
- Customisable displays

**OPT-3-OPPAD-IN**


ASHRAE **BACnet**  
MS/TP  
built-in as standard





Energy efficient pumping with **OPTIFLOW™**

## OptiTools Studio



### Powerful PC Software

Drive commissioning and parameter backup

- Real-time parameter editing
- Drive network communication
- Parameter upload, download and storage
- Simple PLC function programming
- Real-time scope function and data logging
- Real-time data monitoring

### Compatible with:

Windows Vista  
Windows 7  
Windows 8  
Windows 8.1  
Windows 10

### Fieldbus Interfaces



**BACnet/IP**  
OPT-2-BNTIP-IN



**PROFIBUS DP**  
OPT-2-PROFB-IN



**DeviceNet**  
OPT-2-DEVNT-IN



**EtherNet/IP**  
OPT-2-ETHNT-IN



**Modbus TCP**  
OPT-2-MODIP-IN



**PROFINET**  
OPT-2-PFNET-IN



**EtherCAT**  
OPT-2-ETCAT-IN



### Plug-in Options



**Extended I/O**  
OPT-2-EXTIO-IN

- Additional 3 Digital Inputs
- Additional Relay Output

### Cascade Control

**OPT-2-CASCD-IN**  
Additional 3 Relay Outputs

### Mains Isolator



### Mains Isolator Option

Frame Sizes 2 & 3 can be factory ordered with a built in lockable isolator. An optional bolt on isolator is available for Frame Sizes 4 & 5.

#### Product Codes:

**Frame Size 4 = OPT-2-ISOLO-S4**  
**Frame Size 5 = OPT-2-ISOLO-S5**

BACnet MS/TP & Modbus RTU  
on board as standard

Replace # in model code with enclosure/display option

|                                 | kW   | HP  | Amps | Frame Size | Model Code             | Product Family | Generation | Frame Size | Voltage Code | Output Rating | Supply Phases | EMC Filter | Quadrant | IP20 Cabinet Mount | IP55 TFT Display | Indoor IP66 Non Switched | Indoor IP66 with Disconnect | Outdoor IP66 Non Switched | Outdoor IP66 with Disconnect |
|---------------------------------|------|-----|------|------------|------------------------|----------------|------------|------------|--------------|---------------|---------------|------------|----------|--------------------|------------------|--------------------------|-----------------------------|---------------------------|------------------------------|
| 200–240V ± 10%<br>1 Phase Input | 0.75 | 1   | 4.3  | 2          | ODV - 3 - 2 2 0043 - 1 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 1.5  | 2   | 7    | 2          | ODV - 3 - 2 2 0070 - 1 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 2.2  | 3   | 10.5 | 2          | ODV - 3 - 2 2 0105 - 1 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
| 200–240V ± 10%<br>3 Phase Input | 0.75 | 1   | 4.3  | 2          | ODV - 3 - 2 2 0043 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 1.5  | 2   | 7    | 2          | ODV - 3 - 2 2 0070 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 2.2  | 3   | 10.5 | 2          | ODV - 3 - 2 2 0105 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 4    | 5   | 18   | 3          | ODV - 3 - 3 2 0180 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 5.5  | 7.5 | 24   | 3          | ODV - 3 - 3 2 0240 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 7.5  | 10  | 30   | 3          | ODV - 3 - 3 2 0300 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 7.5  | 10  | 30   | 4          | ODV - 3 - 4 2 0300 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             | A-MN                      | E-MN                         |
|                                 | 11   | 15  | 46   | 4          | ODV - 3 - 4 2 0460 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             | A-MN                      | E-MN                         |
|                                 | 15   | 20  | 61   | 5          | ODV - 3 - 5 2 0610 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 18.5 | 25  | 72   | 5          | ODV - 3 - 5 2 0720 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 22   | 30  | 90   | 5          | ODV - 3 - 5 2 0900 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 30   | 40  | 110  | 6          | ODV - 3 - 6 2 1100 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 30   | 40  | 110  | 6A         | ODV - 3 - 6 2 1100 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  |                          |                             |                           |                              |
|                                 | 37   | 50  | 150  | 6          | ODV - 3 - 6 2 1500 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 37   | 50  | 150  | 6A         | ODV - 3 - 6 2 1500 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  |                          |                             |                           |                              |
|                                 | 45   | 60  | 180  | 6          | ODV - 3 - 6 2 1800 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 45   | 60  | 180  | 6B         | ODV - 3 - 6 2 1800 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  |                          |                             |                           |                              |
|                                 | 55   | 75  | 202  | 7          | ODV - 3 - 7 2 2020 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 75   | 100 | 248  | 7          | ODV - 3 - 7 2 2480 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
| 380–480V ± 10%<br>3 Phase Input | 0.75 | 1   | 2.2  | 2          | ODV - 3 - 2 4 0022 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 1.5  | 2   | 4.1  | 2          | ODV - 3 - 2 4 0041 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 2.2  | 3   | 5.8  | 2          | ODV - 3 - 2 4 0058 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 4    | 5   | 9.5  | 2          | ODV - 3 - 2 4 0095 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 5.5  | 7.5 | 14   | 2          | ODV - 3 - 2 4 0140 - 3 | F              | 1          | #          |              |               |               |            |          |                    |                  |                          |                             | A-MN                      | E-MN                         |
|                                 | 5.5  | 7.5 | 14   | 3          | ODV - 3 - 3 4 0140 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        |                           |                              |
|                                 | 7.5  | 10  | 18   | 3          | ODV - 3 - 3 4 0180 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 11   | 15  | 24   | 3          | ODV - 3 - 3 4 0240 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 15   | 20  | 30   | 3          | ODV - 3 - 3 4 0300 - 3 | F              | 1          | #          |              |               |               |            |          |                    |                  |                          |                             | A-MN                      | E-MN                         |
|                                 | 15   | 20  | 30   | 4          | ODV - 3 - 4 4 0300 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 18.5 | 25  | 39   | 4          | ODV - 3 - 4 4 0390 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             | A-MN                      | E-MN                         |
|                                 | 22   | 30  | 46   | 4          | ODV - 3 - 4 4 0460 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             | A-MN                      | E-MN                         |
|                                 | 30   | 40  | 61   | 5          | ODV - 3 - 5 4 0610 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 37   | 50  | 72   | 5          | ODV - 3 - 5 4 0720 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 45   | 60  | 90   | 5          | ODV - 3 - 5 4 0900 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 55   | 75  | 110  | 6          | ODV - 3 - 6 4 1100 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 55   | 75  | 110  | 6A         | ODV - 3 - 6 4 1100 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  |                          |                             |                           |                              |
|                                 | 75   | 100 | 150  | 6          | ODV - 3 - 6 4 1500 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 75   | 100 | 150  | 6A         | ODV - 3 - 6 4 1500 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  |                          |                             |                           |                              |
|                                 | 90   | 150 | 180  | 6          | ODV - 3 - 6 4 1800 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 90   | 150 | 180  | 6B         | ODV - 3 - 6 4 1800 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  |                          |                             |                           |                              |
|                                 | 110  | 175 | 202  | 6B         | ODV - 3 - 6 4 2020 - 3 | F              | 1          | #          |              |               |               |            |          | 2-MN               |                  |                          |                             |                           |                              |
|                                 | 110  | 175 | 202  | 7          | ODV - 3 - 7 4 2020 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 132  | 200 | 240  | 7          | ODV - 3 - 7 4 2400 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 160  | 250 | 302  | 7          | ODV - 3 - 7 4 3020 - 3 | F              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 200  | 300 | 370  | 8          | ODV - 3 - 8 4 3700 - 3 | #              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 250  | 400 | 480  | 8          | ODV - 3 - 8 4 4800 - 3 | #              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
| 500–600V ± 10%<br>3 Phase Input | 0.75 | 1   | 2.1  | 2          | ODV - 3 - 2 6 0021 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 1.5  | 2   | 3.1  | 2          | ODV - 3 - 2 6 0031 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 2.2  | 3   | 4.1  | 2          | ODV - 3 - 2 6 0041 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 4    | 5   | 6.5  | 2          | ODV - 3 - 2 6 0065 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 5.5  | 7.5 | 9    | 2          | ODV - 3 - 2 6 0090 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 7.5  | 10  | 12   | 3          | ODV - 3 - 3 6 0120 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 11   | 15  | 17   | 3          | ODV - 3 - 3 6 0170 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 15   | 20  | 22   | 3          | ODV - 3 - 3 6 0220 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               |                  | X-TN                     | D-TN                        | A-MN                      | E-MN                         |
|                                 | 15   | 20  | 22   | 4          | ODV - 3 - 4 6 0220 - 3 | 0              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 18.5 | 25  | 28   | 4          | ODV - 3 - 4 6 0280 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             | A-MN                      | E-MN                         |
|                                 | 22   | 30  | 34   | 4          | ODV - 3 - 4 6 0340 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             | A-MN                      | E-MN                         |
|                                 | 30   | 40  | 43   | 4          | ODV - 3 - 4 6 0430 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             | A-MN                      | E-MN                         |
|                                 | 37   | 50  | 54   | 5          | ODV - 3 - 5 6 0540 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 45   | 60  | 65   | 5          | ODV - 3 - 5 6 0650 - 3 | 0              | 1          | #          |              |               |               |            |          | 2-MN               | N-MN             |                          |                             |                           |                              |
|                                 | 55   | 75  | 78   | 6          | ODV - 3 - 6 6 0780 - 3 | 0              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 75   | 100 | 105  | 6          | ODV - 3 - 6 6 1050 - 3 | 0              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 90   | 125 | 130  | 6          | ODV - 3 - 6 6 1300 - 3 | 0              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |
|                                 | 110  | 150 | 150  | 6          | ODV - 3 - 6 6 1500 - 3 | 0              | 1          | #          |              |               |               |            |          |                    | N-MN             |                          |                             |                           |                              |


#### EMC Filter

- 0** No Internal EMC Filter
- F** Internal EMC Filter
- R** High Performance EMC Filter


## Drive Specification

|                           |                           |                                                                                                                                                                                                     |
|---------------------------|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input Ratings             | Supply Voltage            | 200 – 240V ± 10%<br>380 – 480V ± 10%<br>500 – 600V ± 10%                                                                                                                                            |
|                           | Supply Frequency          | 48 – 62Hz                                                                                                                                                                                           |
| Output Ratings            | Displacement Power Factor | > 0.98                                                                                                                                                                                              |
|                           | Phase Imbalance           | 3% Maximum allowed                                                                                                                                                                                  |
| Ambient Conditions        | Inrush Current            | < rated current                                                                                                                                                                                     |
|                           | Power Cycles              | 120 per hour maximum, evenly spaced                                                                                                                                                                 |
| Enclosure                 | Temperature               | Storage: –40 to 60°C<br>Operating: –10 to 50°C                                                                                                                                                      |
|                           | Altitude                  | Up to 1000m ASL without derating<br>Up to 2000m maximum UL approved<br>Up to 4000m maximum (non UL)                                                                                                 |
| Programming               | Humidity                  | 95% Max, non condensing                                                                                                                                                                             |
|                           | Vibration                 | Conforms to EN61800-5-1 2007, IEC 60068-2-6                                                                                                                                                         |
| Control Specification     | Ingress Protection        | IP20, IP55, IP66                                                                                                                                                                                    |
|                           | Keypad                    | Built-in keypad as standard<br>Optional remote mountable keypad                                                                                                                                     |
| Fieldbus Connectivity     | Display                   | Built-in multi language text display                                                                                                                                                                |
|                           | PC                        | OptiTools Studio                                                                                                                                                                                    |
| I/O Specification         | Control Method            | Eco Sensorless Vector<br>Open Loop Permanent Magnet Vector<br>Open Loop BLDC Vector<br>Open Loop Synchronous Reluctance Vector                                                                      |
|                           | PWM Frequency             | 4 – 32kHz Effective                                                                                                                                                                                 |
| Maintenance & Diagnostics | Stopping Mode             | Ramp to stop: User Adjustable 0.1 – 600 secs<br>Coast to stop                                                                                                                                       |
|                           | Braking                   | AC Flux Braking                                                                                                                                                                                     |
| Standards Compliance      | Skip Frequency            | Single point, user adjustable                                                                                                                                                                       |
|                           | Setpoint Control          | Analog Signal: 0 to 10 Volts / 10 to 0 Volts<br>–10 Volts to +10 Volts<br>0 to 20mA / 20 to 0mA<br>4 to 20mA / 20 to 4mA<br>Digital: Motorised Potentiometer (Keypad)<br>Modbus RTU<br>BACnet MS/TP |
| Power Supply              | Power Supply              | 24 Volt DC, 100mA, Short Circuit Protected<br>10 Volt DC, 10mA for Potentiometer                                                                                                                    |
|                           | Programmable Inputs       | 5 Total as standard (optional additional 3)<br>3 Digital (optional additional 3)<br>2 Analog / Digital selectable                                                                                   |
| Digital Inputs            | Digital Inputs            | Opto - Isolated<br>8 – 30 Volt DC, internal or external supply<br>Response time < 4ms                                                                                                               |
|                           | Analog Inputs             | Resolution: 12 bits<br>Response time: < 4ms<br>Accuracy: < 1% full scale<br>Parameter adjustable scaling and offset                                                                                 |
| Analog Outputs            | PTC Input                 | Motor PTC / Thermistor Input<br>Trip Level: 3kΩ                                                                                                                                                     |
|                           | Programmable Outputs      | 2 Total<br>1 Analog / Digital<br>1 Relay                                                                                                                                                            |
| Application Features      | Relay Outputs             | Maximum Voltage: 250 VAC, 30 VDC<br>Switching Current Capacity: 5A                                                                                                                                  |
|                           | Analog Outputs            | 0 to 10 Volts / 10 to 0 Volts<br>0 to 20mA / 20 to 0mA<br>4 to 20mA / 20 to 4mA                                                                                                                     |
| Pump Control Features     | PID Control               | Internal PID Controller<br>Multi-setpoint Select<br>Standby / Sleep Mode<br>Boost Function                                                                                                          |
|                           | Fire Mode                 | Bidirectional<br>Selectable Speed Setpoint (Fixed / PID / Analog / Fieldbus)                                                                                                                        |
| Maintenance & Diagnostics | Load Monitoring           | High Current Protection (Fan / Pump Blocked)<br>Low Current Protection (Broken Belt / Shaft)<br>Pump Blockage Detection with Cleaning                                                               |
|                           | Duty / Assist / Standby   | Built-in Multi-Pump Support<br>Automatic Changeover on Fault<br>Automatic Changeover on Time<br>Fully Redundant                                                                                     |
| Standards Compliance      | Pump Blockage Detection   | Pump load monitoring with autotune function, user configurable                                                                                                                                      |
|                           | Pump Cleaning             | Adjustable Bidirectional Pump Cleaning Cycle operation                                                                                                                                              |
| Standards Compliance      | Multi-Pump Control        | Control of fixed speed assist pumps (with cascade control module)<br>Control of Duty, Assist and Standby variable speed pumps via internal Master – Slave network                                   |
|                           | Pump Stir                 | Automatic pump stir to prevent sediment build-up                                                                                                                                                    |
| Standards Compliance      | Fault Memory              | Last 4 Trips stored with time stamp                                                                                                                                                                 |
|                           | Data Logging              | Logging of data prior to trip for diagnostic purposes:<br>Output Current<br>Drive Temperature<br>DC Bus Voltage                                                                                     |
| Standards Compliance      | Maintenance Indicator     | Maintenance Indicator with user adjustable maintenance interval<br>Onboard service life monitoring                                                                                                  |
|                           | Monitoring                | Hours Run Meter<br>Resettable & Non-Resettable kWh meters<br>Cooling Fan Run Time                                                                                                                   |
| Standards Compliance      | Low Voltage Directive     | 2014/35/EU                                                                                                                                                                                          |
|                           | EMC Directive             | 2014/30/EU                                                                                                                                                                                          |
| Standards Compliance      | Additional Conformance    | UL, cUL, EAC, RCM                                                                                                                                                                                   |
|                           | Harmonic Currents         | IEC61000-3-12                                                                                                                                                                                       |
| Standards Compliance      | Environmental Conditions  | Designed to meet IEC 60721-3-3, in operation:<br>IP20 Drives: 3S2/3C2<br>IP55 & 66 Drives: 3S3/3C3                                                                                                  |

## Model Code Guide



## Connection Diagram



NOT TO SCALE

|      |        | IP20 |     |     |      |     |     |       | IP66 |     |     |  | IP55 |     |     |      |      |
|------|--------|------|-----|-----|------|-----|-----|-------|------|-----|-----|--|------|-----|-----|------|------|
| Size |        | 2    | 3   | 4   | 5    | 6A  | 6B  | 8     | 2    | 3   | 4   |  | 4    | 5   | 6   | 7    | 8    |
| mm   | Height | 221  | 261 | 418 | 486  | 614 | 726 | 974   | 257  | 310 | 360 |  | 450  | 540 | 865 | 1280 | 1334 |
| mm   | Width  | 110  | 131 | 172 | 233  | 286 | 330 | 444   | 188  | 211 | 240 |  | 171  | 235 | 330 | 330  | 444  |
| mm   | Depth  | 185  | 205 | 240 | 260  | 320 | 320 | 423   | 182  | 235 | 271 |  | 252  | 270 | 332 | 358  | 423  |
| kg   | Weight | 1.8  | 3.5 | 9.2 | 18.1 | 32  | 43  | 124.5 | 3.5  | 6.6 | 9.5 |  | 11.5 | 23  | 55  | 89   | TBC  |

## Optidrive Eco Pump

### ✓ Saving Energy / Reducing CO<sub>2</sub>

With large scale increases in global energy costs and the introduction of taxes and legislation relating to the industrial production of CO<sub>2</sub> gases the need to reduce energy consumption and save money has never been greater. Optidrive Eco Pump can be used with environmental sensors to reduce pump speed in pumping applications without compromising the required output of the system.

### ✓ Easy Installation

Compact and modern design utilising the latest available technology have accumulated in a robust Eco Pump drive with small dimensions and innovative mounting and cabling features.

### ✓ Simple Set-up & Rapid Commissioning

Optidrive Eco Pump was developed from concept for ease of use. A handful of parameters configure the drive for basic pump applications. A short, concise product data means the drive is running in seconds. Advanced powerful functionality is equally easily accessible.

### ✓ Imaginative Enclosure Design

With a selection of IP55 and IP66 enclosures, Optidrive Eco Pump is well suited to harsh environments, or where cabinet and cabling costs need to be reduced.

### ✓ Advanced Pump Control Functions

The key pump control functionality required for your application is inbuilt into Optidrive Eco Pump and packaged to be both quick and simple to activate. Added to this is the drive's own PLC programming flexibility that makes drive functionality virtually limitless.

### ✓ Options for Flexibility

Optidrive Eco Pump combines both peripheral and factory built options to ensure you get the right drive, scaled to suit your application. With inbuilt BACnet and Modbus, and a host of communication options the Optidrive can integrate easily into your industrial network of choice.



UK Headquarters, Welshpool

Invertek Drives Ltd is dedicated to the design, manufacture and marketing of electronic variable speed drives. The state of the art UK headquarters houses specialist facilities for research & development, manufacturing and global marketing. The company pledges to implement and operate the ISO 14001 Environmental Management System to enhance environmental performance.

All company operations are accredited to the exacting customer focused ISO 9001:2008 quality standard. The company's products are sold globally in over 80 different countries. Invertek Drives' unique and innovative drives are designed for ease of use and meet with recognised international design standards.

## Global Pump Solutions

Invertek Drives operate at the heart of pumping systems around the world



### IRELAND

Maintaining pressure at pumping stations



### HOLLAND

Hot water pumping across district network



### ITALY

Cooling loop flow & temperature control



### AUSTRALIA

Improved reliability & running costs



[www.invertekdrives.com/pump-control](http://www.invertekdrives.com/pump-control)

**INVERTEK DRIVES LIMITED** UK Headquarters

Offa's Dyke Business Park  
Welshpool, Powys, UK  
SY21 8JF

**Tel:** +44 (0)1938 556868  
**Fax:** +44 (0)1938 556869  
**Email:** [sales@invertekdrives.com](mailto:sales@invertekdrives.com)

